

**Amendments to the Specification:**

Please replace paragraph [0016] with the following:

The clamping plate is provided with first lower contact faces 30 located under the pivot pin 22 and second upper contact faces 31 located above the pivot pin 22. Although only one of these is visible in FIG. 4, it will easily be understood that the clamping plate is provided with a corresponding face in the area hidden by the wall 19. The walls 18 and 19 are provided respectively with second lower contact faces 32 (only one of which is visible in the figure), which interact with the first lower contact faces 30 and first upper contact faces 33, which faces, in turn, interact with the second upper contact faces 31.

Please replace paragraph [0017] with the following:

FIG. 5 shows the interaction of the contact faces. The figure shows the foot part mounted on a roof edge area 5. The clamping plate 9 grips a body fold 11 with its gripping means 10 and the clamping plate 9 is tightened upward in the direction indicated by the double arrow P. The interaction which occurs between the ~~lower contact faces 30 and 32~~ the first lower contact faces 30 and the second lower contact faces 32 and the ~~upper contact faces 31 and 33~~ first upper contact faces 33 and second upper contact faces 31, respectively, prevents the clamping plate from turning about the pivot pin 22 in the clockwise direction, which direction is indicated by the arrow U, ensuring that the gripping means 10 does not lose its grip on the body fold 11.